



[Features]

- Vandal resistance up to 750 kg of impact
- 312x zoom (26x optical and 12x digital zoom)
- Pan speed: 430°/sec; tilt speed: 200°/sec
- Accurately pan at +/- 0.02°
- Supports 256 presets and four (4) 6-minute programmable tours
- Supports 24x privacy zones and schedules
- Motion detection, 6 alarm inputs, 1 alarm output
- IP67 compliant water proofing

[Application & Benefits]

i3 International is introducing a new vandal resistant dome camera i3S730PTZP. It is ideal for installations where structural integrity and resistance to vandalism are a priority.

The i3S730PTZP is an IP67 waterproof vandal resistant speed dome camera. This camera is made for rugged conditions and is ideal for high-security installations. With 26x optical zoom and 12x digital zoom, i3S730PTZP provides a clear picture from great distances with its 3.5 to 91mm lens.

In addition, this camera's stepping motor and speed-optimized microprocessor allow users to pan the speed dome with the +/- 0.02° accuracy. The i3S730PTZP is built with precision panning and produces outstanding images.

This camera allows simple setup of up to 256 preset positions and up to four 6-minute tours, which makes it one of the most versatile speed dome cameras in its class. Each preset can be maximized by the camera's 360° auto flip function. The i3S730PTZP camera comes with an automatic day/night mode function, which allows the camera to switch to color mode during the day time and to black/white imaging at night for better night-time viewing performance.

The main advantage of the i3S730PTZP is an easy installation, simplified with a single cable for power, video, and communication. Installation and the i3S730PTZP is simple as 1-2-3!



©2009 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

i3S730PTZ daVinci III series Specifications

Camera	
Video Format	NTSC/PAL
Scanning System	2:1 Interlace V: 59.94Hz, H: 15.734KHz/2:1 Interlace V: 50Hz, H: 15.625KHz
Synch System	Internal / line lock
View Angle	54.2° (wide end) to 2.2° (tele end)
Day & Night (ICR)	Auto / manual
Image Sensor	1/4" SONY Ex-view HAD CCD
Horizontal Resolution	560 TV lines
Number of Effective Pixels	380K pixels/440K pixels approx. (HxV)
Motion detection	Yes
Password protection	Alphanumerical Dome OSD setup protection
Focus Mode	Auto (sensitivity: normal, low), one-push AF, manual, infinity, interval AF, zoom trigger AF
Focusing system	Auto (normal sensitivity / low sensitivity)
Min. Illumination	Normal mode: 0.1 lux (F1.6, 1/60(1/50) sec. ICR OFF, 10 IRE) Slow shutter mode: 0.007 lux (F1.6, 1/4(1/3) sec. ICR OFF, 10 IRE) Night mode: 0.035 lux (F1.6, 1/60(1/50) sec. ICR ON, 10 IRE) Slow shutter mode: 0.0025 lux (F1.6, 1/4(1/3) sec. ICR ON, 10 IRE)
AGC, BLC, Flickerless	AGC: Auto/Manual, BLC: ON/OFF, Flickerless: Yes
Alarm	Auto, ATW, Indoor, outdoor, one-push, manual
Camera Control	More than 50 dB
OSD	Up to 312x (optical 26x, digital 12x)
Zoom limit	ON/OFF (max 1.0S)
Aperture	F1.6 ~ F3.8
Chroma	f=3.5 mm (wide) to 91.0 mm (tele)
Video Compression	1 Vpp composite output, 75 Ohm
Pan/Tilt/Zoom	
Panning range	360° continuous
Tilting range	92°
Preset Speed	Pan: 430°/sec (max); Tilt: 200°/sec (max)
Manual Pan Speed	0.1 - 90°/s, 0.1o/s: max dig. zoom ; 0.4o/s :max opt. zoom
Manual pan speed (turbo)	150°/sec
Manual tilt speed	0.1 - 45°/s, 0.1°/s: max dig. zoom ; 0.4°/s :max opt. Zoom
Auto flip	ON/OFF
Programmable presets	256 points
Programmable tours	4 pattern tours memorizing up to 6 minutes of manual control
Privacy mask	ON/OFF, up to 24 zones (3D Privacy Zone)
Communication	
Protocol	MESSOA P/D (Supports Pelco - P/D, GE, Bosch, Ernitec)
Baud rate	2400, 4800, 9600, 19200 bit/s (DIP-switch selectable)
Environment	
Weight	3800g approx
Operating Temperature	-40 °C ~ 60° C
Storage Temperature	-20°C ~ 60° C
Humidity	20% ~ 80% RH
Dimensions	216.6mm (Ø) X 324.0mm (H)
Vandal Resistant	750KG (1653 lb) impact resistance
Water proof	IP67 (With heater and blower)
Electrical	
Alarm	6 inputs / 1 output
RS-485	Interface
Power Requirement	AC24V ± 10%
Power Consumption	46W (max.)
Electric Shutter	1/1 to 1/10,000sec. 22 Steps
Warranty	
Product Warranty	1 year