



[Features]

- Built-in SD card slot for FTP backup
- 1280 X 960 @10-15 fps
- DC12V/AC24V POE

[Application & Benefits]

i3 International is providing our customers with the best possible solutions for the surveillance, security, and the retail market. Megapixel camera is a key technology and i3 is focusing on to improve the overall efficiency of i3 systems so that our customers can benefit from unparalleled imaging, recording, and sharing of data. i3 is introducing the AX401C1M.

AX401C1M is a 1.3 megapixel 1/3" Sony progressive scan CCD IP camera giving a resolution of 1280x960. AX401C1M is fully integrated with SRX-Pro or iP-Pro software optimizing image quality and bandwidth efficiency usage. The AX401C1M can also stream video using IE 6.0 or 7.0. AX401C1M provides dual streaming MPEG-4 & Motion JPEG.

AX401C1M has built-in Power over Ethernet (PoE) IEEE802.3af, which supplies power to the camera using the network cable, reducing the cost of installation. For installation flexibility the unit also includes a 24 VAC connector. The camera has a BNC video output for simultaneous viewing during installation and maintenance.

i3 International produces a range of camera products applicable for many retail, commercial and industrial applications. From our standard color digital fixed models with day/night capability to full 3-axis pan/tilt/zoom performance, our cameras offer tremendous value to security and loss prevention professionals. To learn more about our selection of cameras and features, please visit our website at www.i3international.com.



©2009 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

Annexus 401C1M MegaPixel Camera Specifications

Camera	
Signal System	Internal
Image Sensor	1/3" progressive transfer CCD
Lens	Optional Mega-Pixel Lens: f=2.4 ~ 6mm, F1.2, f=3.0 ~ 8 mm, F1.0, f=5 ~ 50mm F1.4
Lens Mount	CS mount
Frame rate	Motion Jpeg: SXVGA 1280 X 960 @15 fps VGA (640 X 480)@30fpsMPEG-4:VGA 640x 480 @30fps
Motion detection	Yes
Image Compression Method	MJPEG / MPEG4
BLC	ON/Off
White Balance	2500K ~ 10000K
Angle of view	27.73 ~ 100.18 (H) X 20.45 ~ 73.33 (V)
Software	
Web Browser	IE 6.0 or above, Netscape 7.0 or above
Password Protection	Multiple password for user to login
Communication	
Protocol	TCP/IP, UDP/IP, HTTP, SMTP, DNS, DHCP, NTP, DDNS, FTP, RTP
Environment	
Weight	450g (1 lb)
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Humidity	80% RH or less
Dimensions	180mm x 66mm x 55mm (7.09" x 2.6" x 2.17")
Electrical	
Audio	Two-way mono audio; Full-duplex
Alarm	Yes, 1 x Alarm in, 1 x Alarm out
SD card slot	Yes, SD card up to 2GB supported
Power Requirement	DC12V/AC24V/PoE
Power Consumption	< 8W
Power connector	Screw less Terminal Jack
Electric Shutter	PAL:1/25, 1/50, 1/120, 1/250,1/1000, 1/10000 sec NTSC:1/30, 1/60, 1/120, 1/250,1/1000, 1/10000 sec
Black light compensation	Off, BLC1 ~ BLC6, Auto
Network	
Ethernet	1 x 10/100 base-T Ethernet connection for LAN/WAN
Image compression method	MJPEG / MPEG4
Protocol	TCP/IP, UDP/IP, HTTP, SMTP, DNS, DHCP, NTP, DDNS, FTP, RTP
Connectors	Screw less Terminal Jack
Interface	
Network Port	RJ45 with LEDs
Video Port	BNC
Audio IN & OUT Ports	3.5mm phone jack
Alarm IN & OUT Ports	1x Alarm In / 1x Alarm out
Certifications	
Safety Standard	FCC, CE
Warranty	
Product Warranty	1 year