



[Features]

- Wide angle IR LED lighting
- Waterproof complies with the IP67 standard
- AC24V
- Side opening, easy to install camera
- Die-cast aluminum, resistant to impacts
- 25 kg (55lb) load rating
- Resistant to salt damage
- Sturdy joint
- Internal cable management
- Heater & blower included

[Application & Benefits]

The i3L1070HB turns non-weatherproof cameras into an outdoor rated unit. An excellent visual deterrent in a longer version.

i3 International produces a range of camera and DVR accessories applicable for many retail, commercial and industrial applications. From aluminum camera brackets to UTP & power Supplies our full line of accessories offer tremendous value to security and loss prevention professionals.

To learn more about our complete line of products, please visit our website or contact our customer care department at 1.866.840.0004.

[Specifications]

- Construction: white, Die-cast Aluminum
- Dimensions & weight: 422hx174dx145w mm, 3500g
- Radiant distance: 70m (230 ft)
- IR LED angle & quantity: 50, 96 units
- Operating temperature: -30C (-22F) ~ 50C (122F)
- Operating humidity: 90% RH (max)
- Storage temperature: -40C (-40F) ~ 60C (140F)
- Power Consumption: 35w (max.)



©2009 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.