



## [Features]

- Vari-Focal
- Wide Angle
- Telephoto Long Focal
- 3 Mega for Megapixel Camera
- DC Auto Iris
- CS Mount
- Metal Mount
- ND Filter
- Long Cable
- Aspherical Lens
- F1.4 Wide Aperture Rate

## [Application & Benefits]

Fujinon's 1/3 , 1/2 , or 2/3 or 1.3 mega, 3 mega, or 5 mega-pixels lenses feature our Mega Pixel Difference which optimizes image resolution on all camera formats.

The D-YV4.3×2.8SA-SA2 High image-quality monitoring with optical performance supports 3 megapixels. The D-YV4.3×2.8SA-SA2 f2.8-12mm wide range accommodates various applications. It is designed to maximize optical performance with high-accuracy aspheric lens, low-dispersion glass, and high refractive-index glass. With a Built-in ND filter of T360, for supporting high sensitivity cameras.



©2009 i<sup>3</sup>International. The i<sup>3</sup> logo is property of i<sup>3</sup>International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

# Megapixel VF 2.8 ~ 12mm Lens Specifications

Specifications	
Zoom	Manual
Focus	Manual
Iris	Auto(DC Type)(*1)
Focal Length (mm)	2.8 ~ 12(4.3×)
Iris Range	F1.4 ~ T360(Equivalent to F360)
Back Focal Distance (in air) (mm)	7.83
Exit Pupil Position (From Image Plane) (mm)	455
Focusing Range (From Front Of The Lens) (m)	8 ~ 0.3
Mount	CS
Mass (kg)	80
Remarks	-With Metal Mount (*1)When power is turned off, iris will automatically close. ·YV4.3×2.8SA-SA2L: Long Cable Type(230mm)
Coil Resistance	Drive Coil 190 Damping Coil 500
Current Consumption	23mA(Max.) at DC 4V
1/3"	
Angle of View	Wide: 100°02' × 74°03' Tele: 23°26' × 17°36'
Object Dimensions at M.O.D.	Wide: 753 × 476 Tele: 131 × 98
1/4"	
Angle of View	Wide: 74°03' × 55°06' Tele: 17°36' × 13°13'
Object Dimensions at M.O.D.	Wide: 476 × 329 Tele: 98 × 73