




i3S700PTZ daVinci III series Accessory options

Pendant Mount

- i3D702 Pendant Pipe Mount



i3D702



i3D707

Horizontal Wall Mount

- i3D703 Wall Mount Bracket



i3D703



i3D708

Parapet

- i3D706 parapit Wall Mount



i3D706



i3D760

Corner Mount

- i3D707 Wall Mount Bracket

Pole Mount

- i3D708 Pole Adaptor

Joystick Control

- i3D760 Camera Joystick

Accessories Specs

i3D702 Pendant Pipe Mount

Constructoin:	Aluminum + Steel
Color:	White
Dimensions:	120mm x 268mm x 214mm
Weight:	2.1 Kg
Environment:	Indoor or outdoor mounting

i3D703 Simple Wall Mount Bracket

Constructoin:	Aluminum
Color:	White
Dimensions:	140mm W x 223mm H x 246mm D
Weight:	1.4kg
Environment:	Indoor or outdoor mounting

i3D706 parapit Wall Mount

Constructoin:	Stainless steel
Color:	White
Dimensions:	280mm x 954mm x 445mm
Weight:	5.4kg
Environment:	Indoor or outdoor mounting

i3D707 Corner adaptor

Constructoin:	Aluminum
Color:	White
Dimensions:	377mm W x 260mm H x 179mm D
Weight:	1Kg
Environment:	Indoor or outdoor mounting

i3D708 Pole Adaptor

Constructoin:	Aluminum
Color:	White
Dimensions:	240mm W x 260mm H x 59.6mm D
Weight:	1Kg
Environment:	Indoor or outdoor mounting

i3D760 Camera Joystick

Keypad:	Mechanical
Joystick:	2-axis, vector-solving, auto return to center
Led Display:	Green LED, 7-segment display, 3 cells
Shift indicator:	Red LED
Power Requirement:	DC12V / AC24V
Power Consumption:	1.2 kg (2.65 lbs) approx.
Interface:	RS-485 / RS-422 / RS-232
Protocol:	Pelco-P, Pelco-D
Baud Rate:	1200, 2400, 4800, 9600
Communication Parameters:	8 data bits, no parity, 1 stop bit
Remote Control:	RJ45, 8-pin, modular (female)
Connect to PC:	RS232, D-sub 9-pin (female)
Operating Temperature:	-10° - 50°C (14° - 122°F)
Operating Humidity:	10% ~ 90% RH, no-condensing
Storage Temperature:	-20° - 60°C (-4° - 140°F)
Dimensions (WxHxD):	175mm x 248mm x 55mm (6.8" x 9.76" x 2.17")
Weight:	2.5 W